

















COMPACT, AUTO-FEED, RUGGED METAL TAG EMBOSSER

Designed specifically for the industrial user, the ME1500S is a rugged, reliable and a cost effective solution for the production of embossed metal plates and tags for asset ID and work in progress in the harshest environments. With a 15% increase in production speed, a completely renewed design and new advance features, the ME1500S is an advanced heavy-duty desktop solution that can be integrated into any existing factory and office network.

7" color touchscreen display with high resolution

The ME1500S is equipped with a built-in 7 "WVGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way. The configuration of the machine can be protected by password for high security and data protection.

IoT (Internet of Things) remote access and management

- Web services: The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.
- Data transfer: Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

USB (type A, type B), Ethernet and WiFi

The ME1500S can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

User-friendly, versatile and designed specifically for the asset ID and work in progress tag identification needs of mid-size manufacturing, power, utility, oil, gas sectors.



- COMPANIES
- POWER PLANTS
- MANUFACTURING
 OIL REFINERIES
 - CHEMICAL PLANTS
 - UTILITY COMPANIES



- PLANT ID
- WORK IN PROGRESS
- PART MARKING
- COMPONENT ID
- VALVE/PIPE TAGS
- HOSE TAGS
- SERIAL NUMBER TAGS
 ◆ CABLE TAGS

PLATE AND FEEDER

Dimensions

Rectangular tag: $1.8 \div 4.5 \times 0.83 \div 3.5$ in (WxH), Round tag: Ø 0.5 in, dog tag: 2.05 x 1.14 in (WxH)

Stainless steel: 0.0157 in - aluminium: 0.0157 ÷ 0.0354 in

Medical alert tag: 2.24 x 1.26 in (WxH)



rectangular tag





dog tag



medical alert tag

Materials Thickness

0.0157 ÷ 0.0354 in Input hopper 400 tags

External collection tray (FILO) Output hopper

MARKING

Technology **Embossing** Wheel capacity 60 slots

Type set Simplex 2, Block USA, Block 5

Performance 171 tags per hour based on 55 characters

COMMUNICATION AND SOFTWARE

USB 2.0 port (device and host), Ethernet, WiFi Interface

Software Linux based self enclosed software

PowerTag PC application proprietary software Windows 7/8/10

PowerTag USB on USB key for multiple use

Protocol Multiembosser

Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound

50 fields of 42 characters each (Variable, Fixed data, Counters, etc.)

Data format **HARDWARE**

System CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based

Power supply 100 - 117 - 220 - 230 or 240 Volts - 50 or 60 Hz

Power consumption 800 Watt max

Operating environment Temperature: 41 - 104 °F / 5 - 40 °C, relative humidity: 30% - 90% non condensing

VARIOUS

Others Built in touch screen 7", multi-language user interface management: English, Spanish, Italian

Innovative embedded software up-grade system thru pen drive and web server Machine configuration protected by password for high security and data protection

CERTIFICATIONS

UL, FCC, CE, ROHS









